

PRODUCT NO. 4329

DOTLUX Power supply for LED downlight CIRCLE 12W (Art. 2826) emergency power 300mA, flicker free



to the product page

- suitable for emergency power supply
- flicker-free

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	2829
WEIGHT IN KG	0.07
POWER CONSUMPTION IN WATTS	12

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	176 - 240 V AC/DC
OUTPUT CURRENT IN A	0,3
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	80
PROTECTION CLASS	II
OVERVOLTAGE PROTECTION	3750 V
OUTPUT VOLTAGE	25 - 40 DC
INPUT VOLTAGE SPAN	180-264 AC
WARRANTY IN YEARS	5
INPUT VOLTAGE RANGE LUMINAIRE	180-264 AC
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No

Dimensions

length: 96mm
width: 36mm
height: 24mm

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany