

PRODUCT NO. 3456-B-Ware

DOTLUX LED street light BELUGAmicro 38W 4000K without pole adapter



to the product page



Protection class I with integrated overvoltage protection (10,000 V)
Variety of adapters enables mounting on all pole diameters
The multilayer lens optics with CREE® LEDs enable uniform light distribution
Solid cast aluminum housing in RAL 7022 with impact resistance class IK09
Reliable and highly efficient LED driver with a service life of > 80,000h ensures low maintenance costs

PREDECESSOR ARTICLE	2407
WEIGHT IN KG	3.1
POWER CONSUMPTION IN WATTS	38
NET LUMINOUS FLUX IN LUMENS	3880

Dimensions

length: 388mm
width: 190mm
height: 92mm

BEAM ANGLE	135°/50°
PROTECTION CLASS (IP)	IP66
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 80.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 75
MAST SUPPORT	depending on adapter
IK PROTECTION	IK09
PROTECTION CLASS	I
SWITCH CYCLES	> 160.000
OVERVOLTAGE PROTECTION	up to 10000 V
INPUT VOLTAGE SPAN	127-305 V AC
WARRANTY IN YEARS	0
INPUT VOLTAGE RANGE LUMINAIRE	127-305 V AC
ETIM GRUPPEN-ID	EC000062
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No

DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK09
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No