

PRODUCT NO. 3395-040090-B-Ware

DOTLUX LED surface-mounted luminaire GRIDlong 1500x190mm 38W 4000K UGR<16



to the product page

Suitable for flush installation in suspended grid ceilings 620 x 620 mm
 Replaceable LED modules with screwless quick-release fastener
 Solid, powder-coated metal housing
 Fatigue-free working thanks to flicker-free light
 Connection via light terminal or pre-assembled WAGO-Linect connector

WEIGHT IN KG	6.14
POWER CONSUMPTION IN WATTS	38
NET LUMINOUS FLUX IN LUMENS	3500

Dimensions

length: 1500mm
width: 190mm
height: 56mm

BEAM ANGLE	120°
PROTECTION CLASS (IP)	IP40
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
IK PROTECTION	IK05
PROTECTION CLASS	I
GLARE-FREE	UGR < 16
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	0
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No

DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK05
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No