

PRODUCT NO. 4336

LED power supply CC 750mA 40W 30-50V incl. motion and daylight sensor



to the product page



- Three different functions of the high-frequency sensor possible:
 - On/Off function to 100% light intensity via sensor, then 0% light intensity.
 - On/Off function to 100% luminous intensity via sensor with adjustable afterglow duration/power
 - Permanent basic brightness (20% / 35% luminosity) with additional On/Off function to 100% luminosity via sensor with adjustable afterglow duration
- In addition, the following values are adjustable in steps:
 - Range (up to 10 m)
 - daylight sensor - light duration
 - Afterglow duration (none to continuous)
 - Afterglow power (10% / 25%)

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.14	INPUT VOLTAGE	220 - 240 V AC
POWER CONSUMPTION IN WATTS	60	TC TEMPERATURE IN °C	50
		PROTECTION CLASS	II
		SUITED FOR EMERGENCY LIGHTING	No
		OUTPUT VOLTAGE	30 - 50 DC
		INPUT VOLTAGE SPAN	220-240 AC
		DIMMING WITHOUT DIMMER	No
		INPUT VOLTAGE RANGE LUMINAIRE	220-240 AC
		ETIM GRUPPEN-ID	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	Yes
		DIMMING RF	No
		DIMMING TOUCH AND DIM	No
		DIMMING ZIGBEE	No

Dimensions

length: 125mm
width: 35mm
height: 21mm

DIMMING WITH PUSH-BUTTON	Yes
NO DIM FUNCTION	No
SUITABLE FOR EMERGENCY LIGHTING	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
BEG FUNDING	Only relevant in Germany