

PRODUCT NO. 4355-030036

DOTLUX LED light SLIMvario Ø80x160mm 18W 3000K black







to the product page

- Individual design thanks to interchangeable decorative ring and suspension sets that can be combined in different ways
- Natural color perception thanks to high CRI value >90
- Replaceable high-performance reflector doors available as accessories
- High-quality aluminum housing with powder coating

| SUCCESSION ARTICLE | - | BEAM ANGLE | 36 |
|-----------------------------|----------|--|--------------------------|
| | | PROTECTION CLASS (IP) | IP20 |
| WEIGHT IN KG | 0.5 | LIGHT COLOR | white |
| POWER CONSUMPTION IN WATTS | 18 | INPUT VOLTAGE | 220 - 240 V AC |
| NET LUMINOUS FLUX IN LUMENS | max.1800 | SERVICE LIFE | approx. 40.000 h at 25°C |
| LUMEN PER WATT | 100 | COLOR TEMPERATURE IN KELVIN | 3000 |
| | | COLOR-RENDERING-INDEX | CRI > 90 |
| | | POWER FACTOR | 0,9 |
| | | INRUSH CURRENT IN A | 0 |
| Dimensions | | LUMEN PER WATT | 100 |
| | | PROTECTION CLASS | 1 |
| height: 160mm | | VOLTAGE TYPE | AC |
| diameter: 80mm | | HOUSING COLOUR | black |
| | | INPUT VOLTAGE SPAN | 220-240 AC |
| | | WARRANTY IN YEARS | 5 |
| | | INPUT VOLTAGE RANGE LUMINAIRE | 220-240 AC |
| | | ASSORTMENT | Proline |
| | | ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| | | ETIM GROUP IDENTIFICATION NUMBER | EC002892 |
| | | MATERIAL COVER | - |
| | | DIMMING MAINS VOLTAGE MODULATION | Yes |
| | | DIMMING PHASE CUT-OFF | Yes |
| | | NO DIM FUNCTION | Yes |
| | | COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM3 |



| COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE | No |
|---|--------------------------|
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| PULSE DURATION IN μ S | 0 |
| BEG FUNDING | Only relevant in Germany |
| ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE | F |

COLOUR OF LIGHT ADJUSTABLE

No