

PRODUCT NO. 3571-1FW120

DOTLUX LED panel FLATfrost 1195x295mm COLORselect



to the product page

- 3-Step MacAdam Binning - Constant color temperature of all luminaires.
- High number of low-current LEDs guarantee long LED lifetime and consequently low maintenance costs!
- Glare-free, homogeneous and shadow-free light distribution
- Fatigue-free work due to flicker-free light
- Better contrast rendition with very good color rendering and constant color temperature
- White frame and connection cable with plug connector

SUCCESSION ARTICLE	3571-2FW120	BEAM ANGLE	120
PREDECESSOR ARTICLE	3571-040120	PROTECTION CLASS (IP)	IP40
WEIGHT IN KG	2.4	LIGHT COLOR	multicoloured
POWER CONSUMPTION IN WATTS	40	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	max. 4000	COLOR TEMPERATURE IN KELVIN	3000/4000/5700
LUMEN PER WATT	112	COLOR-RENDERING-INDEX	CRI > 92
		POWER FACTOR	0.96
		LUMEN PER WATT	112
		PROTECTION CLASS	II
Dimensions		HOUSING COLOUR	white
length:	1195mm	GLARE-FREE	UGR < 22
width:	295mm	SWITCH CYCLES	> 100.000
height:	9mm	ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Plastic matt/satinized
		DIMMING DEPENDING ON CONTROL GEAR	Yes
		NO DIM FUNCTION	Yes
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
		COLOUR OF LIGHT ADJUSTABLE	Positions
		COMPATIBLE WITH CASAMBI	No

COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-