

PRODUCT NO. 3293-240180

DOTLUX LED luminaire insert LINEAselect 1437mm 25-80W 4000K dimmable 1-10V 120°



to the product page

- Quick-release fasteners for all connections
- Tool-free mounting rail with integrated through-wiring
- Luminaire insert with flexible phase selection and power adjustment via DIP switch on the mains cable
- Optimized transmittance of the diffusing lens
- Self-cooling LED module
- High luminous efficacy thanks to optimized profile design
- Easily replaceable light units with excellent price-performance ratio
- Long service life thanks to oversized cooling
- Suitable for central battery

Adjustable output thanks to POWERselect:

- 12300@ 78W
- 10900@ 70W
- 9400@ 59W
- 7850@ 47W
- 7200@ 43W
- 6100@ 37W
- 5250@ 32W
- 4300@ 26W

SUCCESSION ARTICLE	-	BEAM ANGLE	120
PREDECESSOR ARTICLE	3293-040180	PROTECTION CLASS (IP)	IP40
WEIGHT IN KG	1.665	LIGHT COLOR	white
POWER CONSUMPTION IN WATTS	25-80	INPUT VOLTAGE	186 - 240 AC/DC
NET LUMINOUS FLUX IN LUMENS	max.12300	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	158-165	COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 83
		POWER FACTOR	0,98
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	158-165
		HOUSING COLOUR	white
Dimensions		SUITED FOR EMERGENCY LIGHTING	yes
length: 1437mm		GLARE-FREE	UGR < 25
width: 65mm		SWITCH CYCLES	> 100.000
height: 45mm		WARRANTY IN YEARS	7
		L80/B10	75750
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	75750

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	150000
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic matt/satinized
DIMMING 1-10 V	Yes
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
SUITABLE FOR EMERGENCY LIGHTING	Yes
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
LIFETIME L70/B50 AT 25°C	150000
LIFETIME L90/B10 AT 25°C	37500
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE	B
COLOUR OF LIGHT ADJUSTABLE	No