

PRODUCT NO. 4523-24

LED power supply CV 24V DC 0-20W 0-0,84A not dimmable IP20 ultra flat



to the product page

- Super flat power supply offers a solution for installations that require a compact design.
- Suitable for indoor LED lighting applications
- SELV compliant output
- flicker free design

| | | | |
|-----------------------------------|------|--|----------------|
| SUCCESSION ARTICLE | - | PROTECTION CLASS (IP) | IP20 |
| WEIGHT IN KG | 0.07 | INPUT VOLTAGE | 220 - 240 V AC |
| POWER CONSUMPTION IN WATTS | 0-20 | POWER FACTOR | 0,88 |
| | | INRUSH CURRENT IN A | 0 |
| | | TC TEMPERATURE IN °C | 75 |
| | | PROTECTION CLASS | II |
| | | OVERVOLTAGE PROTECTION | 500 V |
| | | OUTPUT VOLTAGE | 24 DC |
| | | INPUT VOLTAGE SPAN | 198-264 AC |
| | | WARRANTY IN YEARS | 2 |
| | | INPUT VOLTAGE RANGE LUMINAIRE | 198-264 AC |
| | | ETIM GRUPPEN-ID | EC002710 |
| | | DIMMING 0-10 V | No |
| | | DIMMING 1-10 V | No |
| | | DIMMING DALI | No |
| | | DIMMING DMX | No |
| | | DIMMING DSI | No |
| | | DIMMING POTENTIOMETER (INTEGRATED) | No |
| | | DIMMING LINESWITCH | No |
| | | DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| | | DIMMING MAINS VOLTAGE MODULATION | No |
| | | DIMMING PHASE CUT-OFF | No |
| | | DIMMING PROGRAMMABLE | No |
| | | DIMMING RF | No |

Dimensions

length: 120mm

width: 45mm

height: 16mm

| | |
|--|--------------------------|
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| NO DIM FUNCTION | Yes |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| PULSE DURATION IN μS | 0 |
| BEG FUNDING | Only relevant in Germany |