

PRODUCT NO. 2347-1FW180

DOTLUX LED light LUNA IP44 Ø330mm 18W COLORselect



to the product page

3 light colors in one luminaire - The right light color can be set for every application environment.

1. warm white 3.000 K: hotel, store, wellness/spa areas, home & living
2. neutral white 4.000 K: office, gastronomy, industry, sanitary, retirement homes and hospitals
3. daylight white 5.700 K: Industry, meeting rooms, educational institutions, Office

- Frosted cover provides shadow-free light Distribution
- Stable PMMA plastic cover
- Self-cooling LED module
- Integrated luminaire connection with pressure clamp
- Suitable for central battery
- Sustainable, repairable product design

SUCCESSION ARTICLE	2347-2FW180	BEAM ANGLE	180
PREDECESSOR ARTICLE	2347-0FW180	PROTECTION CLASS (IP)	IP44
WEIGHT IN KG	0.6	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	18	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	max. 1950	COLOR TEMPERATURE IN KELVIN	3000/4000/5700
LUMEN PER WATT	108	COLOR-RENDERING-INDEX	CRI > 82
Dimensions		POWER FACTOR	0,5
height: 95mm		IK PROTECTION	IK07
diameter: 330mm		LUMEN PER WATT	108
		PROTECTION CLASS	I
		HOUSING COLOUR	white
		SUITED FOR EMERGENCY LIGHTING	No
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	5
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No

DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK07
SUITABLE FOR EMERGENCY LIGHTING	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No