

PRODUCT NO. 3670-2FW160

DOTLUX LED luminaire LUNAsilver Ø490mm 36W COLORselect IP44



to the product page

- \"COLORselect\": 3 light colors in one luminaire. The right light color can be set for every application environment
1. Warm white 3,000 K: Hotel, store, wellness/spa areas, home & living
 2. Neutral white 4,000 K: Office, gastronomy, industry, sanitary, retirement homes and hospitals
 3. Daylight white 5,700 K: Industry, meeting rooms, educational institutions, office
- Frosted cover provides shadow-free light distribution
 - Stable PMMA plastic cover
 - Self-cooling LED module
 - Integrated luminaire connection with pressure clamp
 - Suitable for central battery (3372-0FW160 and 3670-0FW160 only)
 - With illuminated corona (indirect lighting)
 - Sustainable product design due to easily replaceable components

SUCCESSION ARTICLE	3670-399160	BEAM ANGLE	160
PREDECESSOR ARTICLE	3670-1FW160	PROTECTION CLASS (IP)	IP44
WEIGHT IN KG	1.53	LIGHT COLOR	multicoloured
POWER CONSUMPTION IN WATTS	36	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	max.3500	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	97	COLOR TEMPERATURE IN KELVIN	3000/4000/5700
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK07
Dimensions		LUMEN PER WATT	97
height: 105mm		HOUSING COLOUR	multicoloured
diameter: 490mm		SUITED FOR EMERGENCY LIGHTING	No
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	5
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Plastic, opal
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No

DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK07
SUITABLE FOR EMERGENCY LIGHTING	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COLOUR OF LIGHT ADJUSTABLE	Positions
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	F