

PRODUCT NO. 4671-040140

DOTLUX LED damp-proof luminaire SIMPLY IP54 1160mm 30W 4000K IK10 DALI























- Housing made of shatterproof polycarbonate with frosted cover for shadow-free light distribution
- 5-pole through-wiring with internal luminaire terminal block and two gaskets
- easy-to-maintain modular internal design with highest quality components
- Cable ducts on the back facilitate installation and through-wiring for surface mounting
- Silicone-free
- Sustainable product design due to easily replaceable components
- The large luminous surface made of polycarbonate produces a uniform and at the same time ceiling-brightening light distribution

WEIGHT IN KG 1.9 POWER CONSUMPTION IN WATTS RΠ **NET LUMINOUS FLUX IN LUMENS** 3700 **LUMEN PER WATT** 123

Dimensions

length: 1160mm width: 109mm height: 85mm

BEAM ANGLE 140 PROTECTION CLASS (IP) IP54 LIGHT COLOR white

INPUT VOLTAGE 176 - 240 V AC/DC **SERVICE LIFE** approx. 50.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 4000 **COLOR-RENDERING-INDEX** CRI > 82 **POWER FACTOR** 0,95 **INRUSH CURRENT IN A** IK PROTECTION IK1∩ **LUMEN PER WATT** 123 PROTECTION CLASS **HOUSING COLOUR** white **SUITED FOR EMERGENCY LIGHTING** yes **SWITCH CYCLES** > 100.000

WARRANTY IN YEARS ASSORTMENT Proline

ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015

ETIM GRUPPEN-ID EC002892

MATERIAL COVER Plastic matt/satinized

DIMMING DALI Yes NO DIM FUNCTION No

COLOUR CONSISTENCY (MCADAM ELLIPSE)

IMPACT STRENGTH IK10 SUITABLE FOR EMERGENCY LIGHTING Yes

SDCM6

not required



COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL No POSSIBLE **COMPATIBLE WITH CASAMBI** No COMPATIBLE WITH APPLE HOMEKIT No COMPATIBLE WITH GOOGLE No **ASSISTANT** COMPATIBLE WITH AMAZON ALEXA No PULSE DURATION IN μS 0 BEG FUNDING only relevant in Germany ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE Ε

No

COLOUR OF LIGHT ADJUSTABLE