

PRODUCT NO. 4729-030120

**DOTLUX Wall lamp BEAMO 10W 3000K white**



to the product page

- Rugged, splash-proof design for outdoor use with IP 65 protection
- EasyBase platform allows for simple and quick installation
- Two independently adjustable beam angles with angle indicators allow for uniform lighting effects even on larger projects
- Special light diffuser provides sharp lighting effects with virtually no color distortion
- Particularly insect-friendly lighting thanks to warm white LEDs and asymmetrical light distribution

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	15x120
<b>WEIGHT IN KG</b>	0.566	<b>PROTECTION CLASS (IP)</b>	IP65
<b>POWER CONSUMPTION IN WATTS</b>	10	<b>LIGHT COLOR</b>	white
<b>NET LUMINOUS FLUX IN LUMENS</b>	900	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>LUMEN PER WATT</b>	90	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	3000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,9
		<b>INRUSH CURRENT IN A</b>	0
		<b>LUMEN PER WATT</b>	90
		<b>PROTECTION CLASS</b>	I
		<b>HOUSING COLOUR</b>	white
		<b>SUITED FOR EMERGENCY LIGHTING</b>	yes
		<b>SWITCH CYCLES</b>	> 100.000
		<b>WARRANTY IN YEARS</b>	3
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GRUPPEN-ID</b>	EC002892
		<b>MATERIAL COVER</b>	Plastic, transparent
		<b>DIMMING 0-10 V</b>	No
		<b>DIMMING 1-10 V</b>	No
		<b>DIMMING DALI</b>	No
		<b>DIMMING DMX</b>	No
		<b>DIMMING DSI</b>	No
		<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>Dimensions</b>			
<b>length:</b>	120mm		
<b>width:</b>	97mm		
<b>height:</b>	100mm		

<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	D
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No