

PRODUCT NO. 4730-030120

DOTLUX Wall lamp BEAMO 10W 3000K black



to the product page

- Rugged, splash-proof design for outdoor use with IP 65 protection
- EasyBase platform enables simple and fast installation
- Two independently adjustable beam angles with angle indicators
- Special light diffuser provides sharp lighting effects with virtually no color distortion
- Particularly insect-friendly lighting due to warm white LEDs and asymmetrical light distribution

SUCCESSION ARTICLE	-	BEAM ANGLE	15x120
WEIGHT IN KG	0.49	PROTECTION CLASS (IP)	IP65
POWER CONSUMPTION IN WATTS	10	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	900	INPUT VOLTAGE	220 - 240 V AC
LUMEN PER WATT	90	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	90
		PROTECTION CLASS	I
		HOUSING COLOUR	black
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	3
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Plastic, transparent
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
Dimensions			
length:	120mm		
width:	97mm		
height:	100mm		

DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
COLOUR OF LIGHT ADJUSTABLE	No