

PRODUCT NO. 4733-0FW110

DOTLUX Tracklight STICKtrack 30W 1,2m COLORselect white



to the product page

- One part number - three light colors adjustable by COLORselect
- Natural color perception due to extra high CRI>95 value
- Compact design, ideal for low room heights
- Uniform light distribution for optimum ambient lighting
- Benefit from the large-area illumination of a light band with simple installation in your track rail

SUCCESSION ARTICLE	-	BEAM ANGLE	110
WEIGHT IN KG	0.718	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	30	LIGHT COLOR	multicoloured
NET LUMINOUS FLUX IN LUMENS	max. 3060	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	102	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000/4000/5700
		COLOR-RENDERING-INDEX	CRI > 95
		POWER FACTOR	0,9
Dimensions		INRUSH CURRENT IN A	0
length: 1240mm		LUMEN PER WATT	102
width: 32mm		PROTECTION CLASS	I
height: 52mm		HOUSING COLOUR	white
		SUITED FOR EMERGENCY LIGHTING	yes
		WARRANTY IN YEARS	3
		SIMILAR TO RAL-COLOUR	9016
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001744
		MATERIAL COVER	Plastic matt/satinized
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No

DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
SUITABLE FOR EMERGENCY LIGHTING	Yes
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COLOUR OF LIGHT ADJUSTABLE	Positions
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE	F