

PRODUCT NO. 4747-030120

**DOTLUX LED wall lamp WALLround 25cm 14W 3000K**



to the product page

- High-quality aluminum housing with powder coating in RAL7016
- Robust, water-jet protected design for outdoor use with IP 65 protection
- Glare-free, homogeneous and shadow-free light distribution
- EasyBase platform enables simple and fast installation
- Mounting accessories included
- Insect-friendly lighting due to warm white LEDs

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	120
<b>WEIGHT IN KG</b>	1.63	<b>PROTECTION CLASS (IP)</b>	IP65
<b>POWER CONSUMPTION IN WATTS</b>	14	<b>LIGHT COLOR</b>	white
<b>NET LUMINOUS FLUX IN LUMENS</b>	1050	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>LUMEN PER WATT</b>	75	<b>SERVICE LIFE</b>	approx. 30.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	3000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,95
<b>Dimensions</b>		<b>INRUSH CURRENT IN A</b>	0
<b>height:</b> 65mm		<b>IK PROTECTION</b>	IK08
<b>diameter:</b> 253mm		<b>LUMEN PER WATT</b>	75
		<b>HOUSING COLOUR</b>	gray
		<b>WARRANTY IN YEARS</b>	3
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GRUPPEN-ID</b>	EC002892
		<b>MATERIAL COVER</b>	Plastic matt/satinized
		<b>NO DIM FUNCTION</b>	Yes
		<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
		<b>IMPACT STRENGTH</b>	IK08
		<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
		<b>PULSE DURATION IN µS</b>	0
		<b>BEG FUNDING</b>	Only relevant in Germany

ENERGIEEFFIZIENZKLASSE DER  
LICHTQUELLE EINER LEUCHTE  
COLOUR OF LIGHT ADJUSTABLE

D

No