


PRODUCT NO. 2805-045120

**DOTLUX QUICK-FIX LED exchangeable module Ø15cm 15W 4500K**



to the product page

- Universal MAGNET LED module with integrated driver for quick and easy replacement of light sources in existing ceiling and wall luminaires
- Extra high magnetic feet enable installation above the existing cabling
- Very high efficiency of up to 120lm/W



SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	2805-001
WEIGHT IN KG	0.11
POWER CONSUMPTION IN WATTS	15
NET LUMINOUS FLUX IN LUMENS	1800
LUMEN PER WATT	120

**Dimensions**

**height:** 32mm  
**diameter:** 150mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 20.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4500
POWER FACTOR	0,57
LUMEN PER WATT	120
PROTECTION CLASS	II
VOLTAGE TYPE	AC
SWITCH CYCLES	> 40.000
INPUT VOLTAGE SPAN	185-264 AC
WARRANTY IN YEARS	2
L80/B10	10000
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	185-264 AC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	D
LIFETIME L80/B10 AT 25°C	10000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	20000
ETIM GRUPPEN-ID	EC000996
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1

<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>FLEXIBLE</b>	Nein
<b>SUITABLE FOR TRAFFIC LIGHTS</b>	No
<b>EXTERNAL DRIVER REQUIRED</b>	Yes
<b>SUITABLE FOR CONSTANT VOLTAGE</b>	No
<b>SUITABLE FOR GENERAL LIGHTING</b>	Yes
<b>SUITABLE FOR CONSTANT CURRENT</b>	Yes
<b>SUITABLE FOR RAIL TRAFFIC</b>	No
<b>SUITABLE FOR MATRIX INFORMATION BOARDS</b>	No
<b>SUITABLE FOR VARIABLE ROAD SIGNS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	20000
<b>LIFETIME L90/B10 AT 25°C</b>	5000
<b>LIGHT COLOUR ACCORDING TO EN 12464-1</b>	neutral white 3300 to 5300 K
<b>BEG FUNDING</b>	Only relevant in Germany
<b>LED-BETRIEBSSTROM IN MA</b>	150
<b>SHAPE</b>	Round
<b>COLOUR</b>	White