

PRODUCT NO. 2746-140180

DOTLUX LED tube LUMENPLUS 104,7cm 15W 4000K frosted rotatable end cap special size



PROLINE



to the product page

• **TECHNICAL ADVANTAGES**

- Internal aluminum heat sink enables optimized thermal management
- Polycarbonate cover with UV-protective coating (non-yellowing)
- Future-oriented due to individually replaceable power supply units
- Individually adjustable light beam angle due to patented end cap
- Fail-safe, as each individual LED is controlled separately

• **FURTHER ADVANTAGES OF THE LUMENPLUS TUBES**

- 5 years Dotlux warranty on drivers and LEDs
- Very easy replacement of fluorescent tubes with starter
- Immediately the full, optimal light output after switching on
- LM80 certified LEDs

ENERGY

DOTLUX
2746-140180

A
B
C
D
E
F
G

15
kWh/1000h

2019/2015

SUCCESSION ARTICLE	2746-240180
PREDECESSOR ARTICLE	2746-040180
WEIGHT IN KG	0.24
POWER CONSUMPTION IN WATTS	15
NET LUMINOUS FLUX IN LUMENS	2550
LUMEN PER WATT	170

Dimensions

length: 1047mm

diameter: 28mm

BEAM ANGLE	180
PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 83
INRUSH CURRENT IN A	0
LUMEN PER WATT	170
HOUSING COLOUR	white
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	5
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	C
ETIM GRUPPEN-ID	EC001959
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
PULSE DURATION IN µS	0
LIGHT COLOUR ACCORDING TO EN 12464-1	neutral white 3300 to 5300 K
BEG FUNDING	Only relevant in Germany
COLOUR	White