

PRODUCT NO. 4839-0E27

DOTLUX LED lamp LUNAE27-sensor 1xE27 Ø330 IP44 with sensor



to the product page



- Classic design with stable PMMA plastic cover.
- Mounting on existing drill holes possible (two- or three-hole mounting from 100 to 220 mm hole spacing / Ø) due to universal perforation with longitudinal slots on the base plate. Additional 3-hole mounting with keyholes Ø 260 mm
- Ex works equipped with plug-in E27 socket, which can then be replaced with a more powerful QUICK-FIX module almost without tools (2 screws).
- When using the QUICK-FIX light module, a luminaire is created with a tool-free replaceable LED module
- Compatible with all E27 light sources and connector for QUICK-FIX up to 24 W
- Suitable for use with E27 LED light sources up to 12 W
- Sustainable product design due to easily replaceable components
- Integrated sensor with On/Off function and daylight detection
 - following values are adjustable in steps
 - Range (up to 6m)
 - Daylight sensor
 - Light duration

SUCCESSION ARTICLE	-	INSTALLATION DEPTH IN MM	0
		INSTALLATION OPENING WIDTH IN MM	0
WEIGHT IN KG	0.56	INSTALLATION OPENING LENGHT IN MM	0
		WARRANTY IN YEARS	5
		ASSORTMENT	Proline
		ETIM GRUPPEN-ID	EC000414
Dimensions		SUITABLE FOR HIGH VOLTAGE LUMINAIRES	Yes
		SUITABLE FOR LAMP POWER IN W	20
height: 95mm		SUITABLE FOR LOW VOLTAGE LUMINAIRES	No
diameter: 330mm		WITH SPACE FOR GEAR	Yes
		BEG FUNDING	Only relevant in Germany
		APPLICATION	For slab ceiling
		MATERIAL	Other