

PRODUCT NO. 4859-040240

DOTLUX STUDIObutler 80W 4000K dimmable LED floor lamp, white



to the product page

- Aluminum housing in RAL9006 from the series \"STUDIO\" with heavy U-steel base.
- Integrated presence sensor activates/dims the luminaire to 30% brightness after 10 minutes and deactivates the luminaire after another 10 minutes
- Glare-free, homogeneous and shadow-free light distribution / smooth top surface
- Better contrast rendition with very good color rendition and constant color temperature (3-Step MacAdam Binning)
- 1.5 m connection cable
- Emergency power supply
- The flicker-free light rendering ensures optimum vision, is easy on the eyes for fatigue-free working and creates a pleasant atmosphere in offices, conference rooms and hotels.

| | | | |
|------------------------------------|-------|---|--------------------------|
| SUCCESSION ARTICLE | - | BEAM ANGLE | 120x120 |
| WEIGHT IN KG | 13.25 | LIGHT COLOR | white |
| POWER CONSUMPTION IN WATTS | 80 | INPUT VOLTAGE | 220 - 240 V AC |
| NET LUMINOUS FLUX IN LUMENS | 8800 | SERVICE LIFE | approx. 50.000 h at 25°C |
| LUMEN PER WATT | 110 | COLOR TEMPERATURE IN KELVIN | 4000 |
| | | COLOR-RENDERING-INDEX | CRI > 82 |
| | | POWER FACTOR | 0,95 |
| | | INRUSH CURRENT IN A | 0 |
| | | LUMEN PER WATT | 110 |
| Dimensions | | PROTECTION CLASS | I |
| length: 610mm | | VOLTAGE TYPE | AC |
| width: 310mm | | HOUSING COLOUR | white |
| height: 1950mm | | GLARE-FREE | UGR < 19 |
| | | SWITCH CYCLES | > 100.000 |
| | | INPUT VOLTAGE SPAN | 220-240 AC |
| | | WARRANTY IN YEARS | 5 |
| | | L80/B10 | 50000 |
| | | SIMILAR TO RAL-COLOUR | 9003 |
| | | DIMMING WITHOUT DIMMER | No |
| | | INPUT VOLTAGE RANGE LUMINAIRE | 220-240 AC |
| | | ASSORTMENT | Proline |
| | | ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| | | LIFETIME L80/B10 AT 25°C | 50000 |
| | | LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C | 100000 |
| | | ETIM GRUPPEN-ID | EC000300 |

| | |
|--|---|
| WITH ILLUMINANT | Yes |
| SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1 | Yes |
| SUITABLE FOR NUMBER OF LIGHT SOURCES | 1 |
| LAMP HOLDER | - |
| MATERIAL COVER | Plastic matt/satinized |
| TYPE OF CONTROL GEAR | LED operating device current-controlled |
| WITH CONTROL GEAR | Yes |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | Yes |
| DIMMING DALI | No |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | Yes |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| NO DIM FUNCTION | No |
| LIGHT DISTRIBUTOR | Diffuser lens/optic/panel |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM3 |
| WITH MOVEMENT SENSOR | Yes |
| WITH LIGHT SENSOR | No |
| CONSTANT LIGHT OUTPUT (CLO) | Yes |
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| IFTTT SUPPORT AVAILABLE | No |
| ELECTRICAL CONNECTION WITH CONNECTOR SYSTEM | No |
| LUMINAIRE HEADS FLEXIBLE | No |
| DIRECT-/INDIRECT PROPORTION SEPARATELY CONTROLLABLE | No |
| ADJUSTABLE | Nein |
| EXCHANGEABLE CONTROL GEAR | Yes |
| SUITABLE FOR LAMP POWER IN W | 80 |
| LAMP TYPE | LED exchangeable |
| WITH DIMMER | No |
| WITH PRESENCE INDICATOR | No |
| WITH REFLECTOR | No |
| WITH SWITCH | No |
| WITH SEPARATE READING LIGHT | No |
| MATERIAL | Aluminium |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | No |

| | |
|---|--------------------------|
| DIMMING GPRS | No |
| LIFETIME L70/B50 AT 25°C | 100000 |
| LIFETIME L90/B10 AT 25°C | 25000 |
| PULSE DURATION IN µS | 0 |
| BEG FUNDING | Only relevant in Germany |
| ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE | E |
| COLOUR OF LIGHT ADJUSTABLE | No |
| BEAM ANGLE ADJUSTABLE | No |
| LIGHT SHARING | Symmetric |
| LIGHT OUTLET | Direct/indirect |
| LUMINOUS FLUX ADJUSTABLE | Continuously variable |
| TYPE OF GRID | None |