PRODUCT NO. 4892-040036

DOTLUX LED tracklight SLIMtrack-eco 25W 4000K white

to the product page

- EDISON® brand LED and flicker-free power supply unit
- Excellent price-performance ratio
- Natural color perception due to extra high CRI value
- Die-cast aluminum housing
- Passive cooling system without fan

SUCCESSION ARTICLE	4891-199036	**BEAM ANGLE**	36
		PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.76	**LIGHT COLOR**	white
POWER CONSUMPTION IN WATTS	25	**INPUT VOLTAGE**	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	2500	**SERVICE LIFE**	approx. 50.000 h at 25°C
LUMEN PER WATT	100	**COLOR TEMPERATURE IN KELVIN**	4000
		COLOR-RENDERING-INDEX	CRI > 92
		POWER FACTOR	0,97
		INRUSH CURRENT IN A	0
Dimensions		**LUMEN PER WATT**	100
		PROTECTION CLASS	I
length: 280mm		**HOUSING COLOUR**	white
diameter: 85mm		**SWITCH CYCLES**	> 100.000
		OVERVOLTAGE PROTECTION	1500 V
		WARRANTY IN YEARS	3
		ASSORTMENT	Ecoline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001744
		MATERIAL COVER	Plastic matt/satinized
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No

DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
DREH- /SCHWENKBAR	350° / 90°
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E
COLOUR OF LIGHT ADJUSTABLE	No
ADJUSTABILITY	Rotating and swivelling