

PRODUCT NO. 4921-OFW110

DOTLUX LED light DISC 45W COLORselect



to the product page

- Flexible use as desired: available as ceiling, wall, surface-mounted or pendant luminaire in 3 sizes
- Individually adjustable for a wide range of applications thanks to COLORselect technology and dimmable DALI 2 power supply unit
- Natural color perception thanks to extra high CRI value >92
- Modern powder-coated aluminum housing (white- similar to RAL9003) with stepped luminaire housing 55mm high
- Easy and quick installation via EASYbase platform
- Pleasant feeling of space due to indirect light component (switchable)
- Sustainable product design due to easily replaceable components

SUCCESSION ARTICLE	6262-099090	BEAM ANGLE	110
WEIGHT IN KG	3.37	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	45	LIGHT COLOR	multicoloured
NET LUMINOUS FLUX IN LUMENS	4725	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	105	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000/4000/5500
		COLOR-RENDERING-INDEX	CRI > 92
		POWER FACTOR	0,97
Dimensions		INRUSH CURRENT IN A	0
height: 91mm		IK PROTECTION	IK05
diameter: 433mm		LUMEN PER WATT	105
		PROTECTION CLASS	I
		HOUSING COLOUR	white
		GLARE-FREE	UGR 21
		SWITCH CYCLES	> 100.000
		INPUT VOLTAGE SPAN	176-240 AC/DC
		WARRANTY IN YEARS	5
		L80/B10	100000
		SIMILAR TO RAL-COLOUR	9003
		IMPROVED ATMOSPHERE TECHNOLOGY	yes
		INPUT VOLTAGE RANGE LUMINAIRE	176-240 AC/DC
		ASSORTMENT	Highline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	100000

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	200000
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic, structured
DIMMING WITH PUSH-BUTTON	Yes
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK05
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	Yes
LIFETIME L70/B50 AT 25°C	200000
LIFETIME L90/B10 AT 25°C	50000
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E
COLOUR OF LIGHT ADJUSTABLE	No