

PRODUCT NO. 4941-700

Light management system LED power supply unit 38Watt 700mA CASAMBI dimmable



to the product page

- Independent dimmable dual-channel CASAMBI LED driver
- Automatically establishes a wireless communication network with up to 127 nodes
- Dimming range from 1 - 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- Tunable White applications

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.25	INPUT VOLTAGE	176 - 240 V AC/DC
		Service life	
		OUTPUT CURRENT IN A	0.7
		INRUSH CURRENT IN A	26.4
		TC TEMPERATURE IN °C	75
Dimensions		OUTPUT VOLTAGE	20 - 50 DC
length: 215mm		INPUT VOLTAGE SPAN	198-264 AC
width: 70mm		INPUT VOLTAGE RANGE LUMINAIRE	198-264 AC
height: 31mm		ETIM GRUPPEN-ID	EC002710
diameter: 75mm		NO DIM FUNCTION	No
		PULSE DURATION IN µS	224
		BEG FUNDING	Only relevant in Germany