

PRODUCT NO. 4941-950

Light management system LED power supply unit 38Watt 950mA CASAMBI dimmable



to the product page

- Independent dimmable dual-channel CASAMBI LED driver
- Automatically establishes a wireless communication network with up to 127 nodes
- Dimming range from 1 - 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- Tunable White applications

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.25	INPUT VOLTAGE	176 - 240 V AC/DC
		Service life	
		OUTPUT CURRENT IN A	0,95
		INRUSH CURRENT IN A	26,4
		TC TEMPERATURE IN °C	75
Dimensions		OUTPUT VOLTAGE	20 - 40 DC
length: 215mm		INPUT VOLTAGE SPAN	198-264 AC
width: 70mm		INPUT VOLTAGE RANGE LUMINAIRE	198-264 AC
height: 31mm		ETIM GRUPPEN-ID	EC002710
diameter: 75mm		NO DIM FUNCTION	No
		COMPATIBLE WITH CASAMBI	Yes
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No
		IFTTT SUPPORT AVAILABLE	No
		PULSE DURATION IN µS	224
		BEG FUNDING	Only relevant in Germany