


PRODUCT NO. 4955

**DOTLUX LED continuous row system LINEAcompact Blind unit two-length**



to the product page

Two-length LINEAcompact blind unit.

<b>SUCCESSION ARTICLE</b>	-	<b>PROTECTION CLASS (IP)</b>	IP54
<b>WEIGHT IN KG</b>	3.5	<b>LIGHT COLOR</b>	-
		<b>INPUT VOLTAGE</b>	176 - 240 V AC/DC
		<b>COLOR TEMPERATURE IN KELVIN</b>	-
		<b>INRUSH CURRENT IN A</b>	0
		<b>PROTECTION CLASS</b>	I
<b>Dimensions</b>		<b>VOLTAGE TYPE</b>	AC/DC
<b>length:</b> 2886mm		<b>HOUSING COLOUR</b>	Aluminium
<b>width:</b> 62mm		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
<b>height:</b> 51mm		<b>INPUT VOLTAGE SPAN</b>	176-240 AC/DC
		<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
		<b>SUITABLE FOR MOUNTING</b>	No
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	176-240 AC/DC
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GRUPPEN-ID</b>	EC002892
		<b>WITH ILLUMINANT</b>	No
		<b>SUITABLE FOR WALL MOUNTING</b>	No
		<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
		<b>SUITABLE FOR CEILING MOUNTING</b>	Yes
		<b>SUITABLE FOR LIGHT LINE CONFIGURATION</b>	Yes
		<b>LAMP HOLDER</b>	-
		<b>MATERIAL COVER</b>	-
		<b>TYPE OF GRID</b>	-
		<b>WITH CONTROL GEAR</b>	No

<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	No
<b>LIGHT DISTRIBUTOR</b>	-
<b>LIGHT SHARING</b>	-
<b>BEAM ANGLE</b>	-
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>LIGHT OUTLET</b>	-
<b>LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24</b>	Yes
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>WITH AIR SLOTS</b>	No
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	No
<b>TYPE OF WIRING</b>	Through wiring included
<b>CONNECTION TYPE</b>	Push-in clamp
<b>COLOUR OF LIGHT ADJUSTABLE</b>	-
<b>LUMINOUS FLUX ADJUSTABLE</b>	-
<b>BEAM ANGLE ADJUSTABLE</b>	-
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	No
<b>LAMP TYPE</b>	-
<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN µS</b>	0

**BEG FUNDING**

Only relevant in Germany

**ENERGIEEFFIZIENZKLASSE DER  
LICHTQUELLE EINER LEUCHTE**

-

**SURFACE PROTECTION HOUSING**

Powder coating

**TYPE OF CONTROL GEAR**

Not required