

PRODUCT NO. 4945-050045

DOTLUX LED light band system LINEAcompact 50W narrow beam 1452mm 5000K not dimmable



to the product page



- All units are delivered fully assembled and only need to be plugged together
- Flexible phase selection directly at the luminaire
- Patent-protected LED cover ensures error-free assembly
- High-quality aluminum core board guarantees perfect cooling and a long service life of the LM80 certified LEDs
- Future-proof with replaceable LED module and separate driver

WEIGHT IN KG	2.534	BEAM ANGLE	45
POWER CONSUMPTION IN WATTS	50	PROTECTION CLASS (IP)	IP54
NET LUMINOUS FLUX IN LUMENS	8500	INPUT VOLTAGE	176 - 240 V AC/DC
		Service life	
		COLOR TEMPERATURE IN KELVIN	5000
		COLOR-RENDERING-INDEX	CRI > 82
Dimensions		POWER FACTOR	0,98
length: 1452mm		PROTECTION CLASS	I
width: 66mm		VOLTAGE TYPE	AC
height: 63mm		SWITCH CYCLES	> 200.000
		L80/B10	100000
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	100000
		ETIM GRUPPEN-ID	EC002892
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No

DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No