

PRODUCT NO. 4951-040045

DOTLUX LED trunking system LINEAcompact 50W narrow beam 1452mm 4000K DALI dimmable



to the product page

- All units are supplied fully assembled and only need to be plugged together
- Flexible phase selection directly at the luminaire
- Utility model-protected LED cover ensures error-free assembly
- High-quality aluminum core board guarantees perfect cooling and thus a long service life of the LM80 certified LEDs
- Future-proof with replaceable LED module and separate driver

| | | | |
|------------------------------------|------|---|-------------------|
| SUCCESSION ARTICLE | - | BEAM ANGLE | 45 |
| WEIGHT IN KG | 2.6 | PROTECTION CLASS (IP) | IP54 |
| POWER CONSUMPTION IN WATTS | 50 | LIGHT COLOR | white |
| NET LUMINOUS FLUX IN LUMENS | 8350 | INPUT VOLTAGE | 176 - 240 V AC/DC |
| LUMEN PER WATT | 167 | Service life | |
| | | COLOR TEMPERATURE IN KELVIN | 4000 |
| | | COLOR-RENDERING-INDEX | CRI > 82 |
| | | POWER FACTOR | 0,95 |
| | | INRUSH CURRENT IN A | 0 |
| | | LUMEN PER WATT | 167 |
| Dimensions | | PROTECTION CLASS | I |
| length: 1452mm | | VOLTAGE TYPE | AC/DC |
| width: 66mm | | HOUSING COLOUR | Aluminium |
| height: 63mm | | SUITED FOR EMERGENCY LIGHTING | No |
| | | SWITCH CYCLES | > 200.000 |
| | | L80/B10 | 100000 |
| | | RATED CURRENT | 2.9 |
| | | SUITABLE FOR SURFACE MOUNTING | Yes |
| | | SUITABLE FOR MOUNTING | No |
| | | ASSORTMENT | Proline |
| | | ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| | | LIFETIME L80/B10 AT 25°C | 100000 |
| | | ETIM GRUPPEN-ID | EC002892 |
| | | WITH ILLUMINANT | Yes |
| | | SUITABLE FOR WALL MOUNTING | No |

| | |
|--|---|
| SUITABLE FOR SUSPENDED MOUNTING | Yes |
| SUITABLE FOR CEILING MOUNTING | Yes |
| SUITABLE FOR LIGHT LINE CONFIGURATION | Yes |
| LAMP HOLDER | - |
| MATERIAL COVER | Plastic, transparent |
| TYPE OF CONTROL GEAR | LED operating device current-controlled |
| WITH CONTROL GEAR | Yes |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | Yes |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| DIMMING DEPENDING ON CONTROL GEAR | Yes |
| NO DIM FUNCTION | No |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM6 |
| LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24 | Yes |
| SUITABLE FOR EMERGENCY LIGHTING | No |
| WITH MOVEMENT SENSOR | No |
| WITH LIGHT SENSOR | No |
| COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE | No |
| WITH AIR SLOTS | No |
| TYPE OF WIRING | Through wiring included |
| CONNECTION TYPE | Push-in clamp |
| OPERATION BY BLUETOOTH | No |
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| IFTTT SUPPORT AVAILABLE | No |
| EXCHANGEABLE CONTROL GEAR | Yes |
| SUITABLE FOR LAMP POWER IN W | 50 |
| LAMP TYPE | LED exchangeable |
| EMERGENCY POWER SUPPLY INTEGRATED | No |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |

| | |
|--|--------------------------|
| PULSE DURATION IN μS | 0 |
| BEG FUNDING | only relevant in Germany |
| ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE | D |
| LIGHT OUTLET | Direct |
| COLOUR OF LIGHT ADJUSTABLE | No |
| LUMINOUS FLUX ADJUSTABLE | No |
| BEAM ANGLE ADJUSTABLE | No |
| LIGHT SHARING | Symmetric |
| TYPE OF GRID | None |
| BEAM ANGLE | Wide beam 41-80° |
| SURFACE PROTECTION HOUSING | Other |
| LIGHT DISTRIBUTOR | None |