

PRODUCT NO. 4965-030120

**DOTLUX LED solar wall light FLASHwall with sensor 3.5W 3000K**



to the product page

- Solar lithium-ion battery light with motion sensor (2 selectable operating modes)
- Reliable and fast battery charging thanks to large SOLAR panel, also suitable for indirect light incidence
- Particularly insect-friendly lighting thanks to warm white LEDs and motion sensor
- High-quality, splash-proof aluminum housing with weather-resistant powder coating
- Large, homogeneously designed light surface enables glare-free light distribution
- Easy alignment of the light thanks to adjustable stainless steel mounting bracket
- Includes rechargeable battery (replaceable) and mounting accessories
- Can also be used as a house number light with the house number set

Motion sensor operating modes:

- A) 15% permanent light intensity after sunset, 100% light intensity on movement (duration 15 seconds)
- B) 0% light intensity after sunset, 100% light intensity on movement (duration 15 seconds)

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	120
<b>WEIGHT IN KG</b>	1.8	<b>PROTECTION CLASS (IP)</b>	IP54
<b>POWER CONSUMPTION IN WATTS</b>	3,5	<b>LIGHT COLOR</b>	white
<b>NET LUMINOUS FLUX IN LUMENS</b>	250	<b>SERVICE LIFE</b>	approx. 30.000 h at 25°C
<b>LUMEN PER WATT</b>	71	<b>COLOR TEMPERATURE IN KELVIN</b>	3000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>MOTION SENSOR</b>	Infrared, 6-10m, 120°
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK06
<b>Dimensions</b>		<b>BATTERY RUNTIME</b>	3h at 100% / 20h at 15%
<b>length:</b> 160mm		<b>LUMEN PER WATT</b>	71
<b>width:</b> 180mm		<b>PROTECTION CLASS</b>	III
<b>height:</b> 255mm		<b>HOUSING COLOUR</b>	gray
		<b>WARRANTY IN YEARS</b>	3
		<b>CAPACITIV OF BATTERY IN MAH</b>	1500
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GRUPPEN-ID</b>	EC002892
		<b>MATERIAL COVER</b>	Plastic matt/satinized
		<b>NO DIM FUNCTION</b>	Yes
		<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
		<b>IMPACT STRENGTH</b>	IK06
		<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No

<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	-
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No