


PRODUCT NO. 4993-0FW140

**DOTLUX Mirror light TRENDO 10W 3000/4000/5700K COLORselect**



to the product page

- Modern, stylish design
- Maximum illuminated area without visible screw connections
- EASYbase platform enables quick and easy installation
- Mounting on existing drill holes possible due to free surface on the base plate
- 2 cable inlets pre-installed (individual inlets can be drilled into the aluminum base if required)
- Simply set your desired light color yourself, one article number - three light colors through COLORselect
- Sustainable product design thanks to easily replaceable components

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	140
<b>WEIGHT IN KG</b>	0.64	<b>PROTECTION CLASS (IP)</b>	IP44
<b>POWER CONSUMPTION IN WATTS</b>	10	<b>LIGHT COLOR</b>	multicoloured
<b>NET LUMINOUS FLUX IN LUMENS</b>	1200	<b>INPUT VOLTAGE</b>	186 - 240 AC/DC
<b>LUMEN PER WATT</b>	120	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	3000/4000/5700
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,95
		<b>INRUSH CURRENT IN A</b>	0
<b>Dimensions</b>		<b>IK PROTECTION</b>	IK08
<b>length:</b> 600mm		<b>LUMEN PER WATT</b>	120
<b>width:</b> 85mm		<b>PROTECTION CLASS</b>	I
<b>height:</b> 57mm		<b>VOLTAGE TYPE</b>	AC/DC
		<b>HOUSING COLOUR</b>	multicoloured
		<b>SWITCH CYCLES</b>	> 100.000
		<b>INSTALLATION OPENING WIDTH IN MM</b>	0
		<b>INSTALLATION OPENING LENGHT IN MM</b>	0
		<b>INPUT VOLTAGE SPAN</b>	240
		<b>WARRANTY IN YEARS</b>	5
		<b>L80/B10</b>	50000
		<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
		<b>SUITABLE FOR MOUNTING</b>	No
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	240
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required

LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	0
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR LIGHT LINE CONFIGURATION	No
MATERIAL COVER	Plastic matt/satinized
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
COLOUR OF LIGHT ADJUSTABLE	Positions
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
SUITABLE FOR LAMP POWER IN W	10
LAMP TYPE	LED
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	0
LIFETIME L90/B10 AT 25°C	0
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany

**ENERGIEEFFIZIENZKLASSE DER  
LICHTQUELLE EINER LEUCHTE**

C

**BEAM ANGLE ADJUSTABLE**

No

**BEAM ANGLE**

Extreme wide beam >80°