


PRODUCT NO. 1665-230360NANO

DOTLUX LED street lamp RETROFITnano E27 18W 3000K



to the product page

- Waterproof nano-coating IP65 with fully potted driver module.
- Overvoltage protection up to 4,000 V
- No early failures: SecureSolderConnect technology prevents hairline cracks and cold solder joints
- Unique: Integrated, temperature-dependent power regulation to 50% to protect against overheating
- AirFin-Cooling: 2.5 times larger cooling surface than comparable products and up to 20% reduced weight at lamp base
- Easy replacement with Retro-Fit E27 base for common HQL/NAV lamps
- Lamp can be operated without conversion on HQL Voschlat devices and also directly on 230V. NAV ballasts must be disconnected
- Optimally arranged LEDs enable uniform light distribution
- Lamp efficiency of up to 130 lm / W due to the use of high quality Lm80 certified LEDs



SUCCESSION ARTICLE	-	BEAM ANGLE	360
PREDECESSOR ARTICLE	1665-130360NANO	PROTECTION CLASS (IP)	IP65
WEIGHT IN KG	0.35	INPUT VOLTAGE	100 - 240 V AC
POWER CONSUMPTION IN WATTS	18	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	2700	BASE	E27
LUMEN PER WATT	150	COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 80
		POWER FACTOR	0,9
		INRUSH CURRENT IN A	45
		LUMEN PER WATT	150
		HOUSING COLOUR	white
		SUITED FOR EMERGENCY LIGHTING	yes
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	5
		ENEC-CERTIFIED	ENEC 05
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	D
		ETIM GRUPPEN-ID	EC001959
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		SUITABLE FOR EMERGENCY LIGHTING	Yes
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No
		LIFETIME L90/B10 AT 25°C	17000
		PULSE DURATION IN µS	50

Dimensions

height: 166mm
diameter: 73mm

**LIGHT COLOUR ACCORDING TO EN
12464-1**

BEG FUNDING

COLOUR

warm white <3300 K

Only relevant in Germany

White