

PRODUCT NO. 5043

LED power supply CC for QUICK-FIXdc 15-50W 350-1400mA 25-54V non-dimmable NFC linear pre-programmed outputs 350/700/1050/1400mA



to the product page

- SELV output protection for safety and flexibility in luminaires
- Very low current ripple, according to IEEE 1789 recommendation
- NFC technology for wireless programming
- Wide selection range for fixed current output
- Suitable for use in emergency lighting applications
- Active no-load protection
- Long life of up to 100,000 hours
- Ideal solution for Class I and Class II luminaires

Adjustable operating current: 350/700/1050/1400mA

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
PREDECESSOR ARTICLE	4226	INPUT VOLTAGE	186 - 240 AC/DC
WEIGHT IN KG	0.198	OUTPUT CURRENT IN A	0,35-1,4
POWER CONSUMPTION IN WATTS	15-50	INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	80
		PROTECTION CLASS	II
		OVERVOLTAGE PROTECTION	1000 V
		INPUT VOLTAGE SPAN	198-264 AC / 186-280 DC
		WARRANTY IN YEARS	5
		INPUT VOLTAGE RANGE LUMINAIRE	198-264 AC / 186-280 DC
		ETIM GROUP IDENTIFICATION NUMBER	ECC002710
Dimensions		DIMMING 0-10 V	No
length: 280mm		DIMMING 1-10 V	No
width: 30mm		DIMMING DALI	No
height: 21mm		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No

DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany