

PRODUCT NO. 5055-040180

**DOTLUX LED light LUNAbasic-sensor IP44 Ø330mm 18W 4000K**



to the product page

- Frosted cover provides shadow-free light distribution
- Stable PMMA plastic cover
- Aluminum core board
- 3-pole quick-connect terminal
- Splash-proof luminaire IP44
- Integrated luminaire connection with pressure clamp
- Sustainable product design due to easily replaceable components

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	180
<b>WEIGHT IN KG</b>	0.45	<b>PROTECTION CLASS (IP)</b>	IP44
<b>POWER CONSUMPTION IN WATTS</b>	18	<b>LIGHT COLOR</b>	white
<b>NET LUMINOUS FLUX IN LUMENS</b>	1260	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>LUMEN PER WATT</b>	70	<b>SERVICE LIFE</b>	approx. 30.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	4000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,5
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK03
		<b>LUMEN PER WATT</b>	70
		<b>PROTECTION CLASS</b>	I
		<b>VOLTAGE TYPE</b>	DC
		<b>HOUSING COLOUR</b>	white
		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
		<b>WARRANTY IN YEARS</b>	2
		<b>RATED CURRENT</b>	0.15
		<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
		<b>ASSORTMENT</b>	Ecoline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GROUP IDENTIFICATION NUMBER</b>	EC002892
		<b>WITH ILLUMINANT</b>	Yes
		<b>SUITABLE FOR WALL MOUNTING</b>	Yes
		<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
		<b>SUITABLE FOR CEILING MOUNTING</b>	Yes
<b>Dimensions</b>			
<b>height:</b>	100mm		
<b>diameter:</b>	330mm		

SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	other Without
MATERIAL COVER	Plastic, opal
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK03
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	Yes
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	19.8
LAMP TYPE	LED not exchangeable
DIMMING DALI-2	No

<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE</b>	F
<b>LIGHT OUTLET</b>	Direct
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>SURFACE PROTECTION HOUSING</b>	Plastic-coated
<b>TYPE OF GRID</b>	None
<b>TYPE OF CONTROL GEAR</b>	Not required
<b>BEAM ANGLE</b>	Open beam/diffuse