

PRODUCT NO. 5030-1

LED power supply CC 350-1050mA 40W 2-100V dimmable KNX/Push







to the product page



• Constant current power supply, which can be preset by DIP switch between 350 and 1050mA.

SUCCESSION ARTICLE

WEIGHT IN KG 0.248
POWER CONSUMPTION IN WATTS 40

Dimensions

length: 124mm width: 82mm height: 23mm INPUT VOLTAGE 220 - 240 V AC

OUTPUT CURRENT IN A 0,35-1,05

INRUSH CURRENT IN C 90

PROTECTION CLASS II

OVERVOLTAGE PROTECTION3750 VOUTPUT VOLTAGE2 - 100 DC

INPUT VOLTAGE SPAN 180-295 AC / 220-417 DC

WARRANTY IN YEARS 2

INPUT VOLTAGE RANGE LUMINAIRE 180-295 AC / 220-417 DC

 ETIM GROUP IDENTIFICATION NUMBER
 EC002710

 DIMMING PROGRAMMABLE
 Yes

 DIMMING WITH PUSH-BUTTON
 No

 NO DIM FUNCTION
 No

 COMPATIBLE WITH CASAMBI
 No

 COMPATIBLE WITH APPLE HOMEKIT
 No

 COMPATIBLE WITH GOOGLE ASSISTANT
 No

COMPATIBLE WITH AMAZON ALEXA No PULSE DURATION IN μS

BEG FUNDING Only relevant in Germany