

PRODUCT NO. 5143-030120

DOTLUX LED spotlight FLOORslim 50W 3000K white



to the product page

- Solid, waterproof, die-cast aluminum housing with efficient cooling and high quality powder coating from Akzo Nobel.
- Reliable operation due to branded LEDs from LUMILEDS and capacitor-less power supply with 2kV overvoltage protection
- ESG safety glass - ULTRA CLEAR - highly transparent glass for excellent light color and improved light output
- Curved mounting bracket allows easy installation without disassembling the bracket (freely rotatable 320°)
- Incl. 1m white UV stable rubber cable (H05RN-F open ends)

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3198-030120
WEIGHT IN KG	0.85
POWER CONSUMPTION IN WATTS	50
NET LUMINOUS FLUX IN LUMENS	5650
LUMEN PER WATT	113

Dimensions

length: 239mm
width: 192mm
height: 44mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
IK PROTECTION	IK08
LUMEN PER WATT	113
PROTECTION CLASS	I
VOLTAGE TYPE	AC
HOUSING COLOUR	white
OVERVOLTAGE PROTECTION	2000 V
WARRANTY IN YEARS	3
L80/B10	35000
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	35000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	70000
ETIM GROUP IDENTIFICATION NUMBER	EC001744
MATERIAL COVER	Glass transparent
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No

DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	70000
LIFETIME L90/B10 AT 25°C	20000
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ROTATABLE / SWIVELLING	Mounting bracket freely rotatable 320°
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	E
COLOUR OF LIGHT ADJUSTABLE	No
ADJUSTABILITY	Swivelling