

PRODUCT NO. 5068-1

LED power supply CC 15-44W 300-1050mA 6-52V PUSH dimmable DALI-2 suitable for central battery through-wireable



to the product page

- The power supply is dimmable via DALI-2
- With the constant current technology (CC) it is suitable for luminaires with constant current
- The connected constant current luminaires can be dimmed between 1%-100%
- The output current is adjustable:
300/350/400/450/500/550/600/650/700/750/800/850/900/950/1000/1050mA
- The power supply is set to 950mA by default
- Suitable for use in emergency lighting systems

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
PREDECESSOR ARTICLE	5068	INPUT VOLTAGE	176 - 240 V AC/DC
WEIGHT IN KG	0.21	OUTPUT CURRENT IN A	0,35-1,05
POWER CONSUMPTION IN WATTS	12-40	INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	90
		PROTECTION CLASS	II
		Output voltage	
Dimensions		INPUT VOLTAGE SPAN	176-264 AC / 170-275 DC
length: 170mm		WARRANTY IN YEARS	3
width: 65mm		DIMMING WITHOUT DIMMER	No
height: 30mm		INPUT VOLTAGE RANGE LUMINAIRE	176-264 AC / 170-275 DC
		ETIM GROUP IDENTIFICATION NUMBER	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	Yes
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	Yes
NO DIM FUNCTION	No
CONSTANT LIGHT OUTPUT (CLO)	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR DC-VOLTAGE (PRIMARY SIDE)	No
SUITABLE FOR CONSTANT CURRENT	Yes
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany