

PRODUCT NO. 5333

DOTLUX LED power supply 220-240VAC CB 400mA-700mA 16-28W



to the product page

- LED Power Supply for LED Panels 950mA
- With constant current (CC) technology, it is suitable for constant current luminaires
- The output current is adjustable: 400/500/600/700mA
- The power supply is set to 700mA by default

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4330 + 3573-1
WEIGHT IN KG	0.126
POWER CONSUMPTION IN WATTS	16-28

Dimensions

length: 152mm
width: 48mm
height: 29mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	186 - 240 AC/DC
OUTPUT CURRENT IN A	400-700 mA
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	85
PROTECTION CLASS	II
SUITED FOR EMERGENCY LIGHTING	yes
OUTPUT VOLTAGE	25 - 40 DC
WARRANTY IN YEARS	3
ETIM GROUP IDENTIFICATION NUMBER	EC002710
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany