

PRODUCT NO. 5334

DOTLUX LED power supply CC 600mA-1050mA 24-42W 220-240V



to the product page

- LED Power Supply for LED Panels 950mA
- With constant current (CC) technology, it is suitable for constant current luminaires
- The output current is adjustable: 600/700/950/1050mA
- The power supply is set to 950mA by default

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	2840-1+5036
WEIGHT IN KG	0.13
POWER CONSUMPTION IN WATTS	24-42

Dimensions

width: 48mm
height: 29mm
length: 152mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	186 - 240 AC/DC
OUTPUT CURRENT IN A	0,6-1,05
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	90
PROTECTION CLASS	II
SUITED FOR EMERGENCY LIGHTING	yes
OUTPUT VOLTAGE	25 - 40 DC
INPUT VOLTAGE SPAN	198 - 264 AC/DC
WARRANTY IN YEARS	3
INPUT VOLTAGE RANGE LUMINAIRE	198 - 264 AC/DC
ETIM GROUP IDENTIFICATION NUMBER	EC002710
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany