


PRODUCT NO. 5363-040120

**DOTLUX LED panel RIMLESS 620x620x max.42W 1050mA 4000K**



to the product page

- Save even more energy with highly efficient LEDs with a luminous efficacy of 165Lm/W
- Frameless design for large-area illumination (also great for SKYLIGHT motifs)
- Homogeneous luminous surface with frosted cover provides pleasant light distribution
- Easy to install and service thanks to DC system plug (Plug&Play compatible with all DOTLUX power supplies)

Power consumption with through-wired power supply Art. 5334

45W @1050 mA = 6950Lm

42W @ 950 mA = 6490Lm

30W @ 700 mA = 4800Lm

26W @ 600 mA = 4120Lm

This product is compatible with our surface mount frame 5226.

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	120
<b>WEIGHT IN KG</b>	1.756	<b>PROTECTION CLASS (IP)</b>	IP40
<b>POWER CONSUMPTION IN WATTS</b>	max. 42	<b>LIGHT COLOR</b>	white
<b>LUMEN PER WATT</b>	max.178	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>NET LUMINOUS FLUX IN LUMENS</b>	max. 6950	<b>COLOR TEMPERATURE IN KELVIN</b>	4000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK02
		<b>LUMEN PER WATT</b>	max.178
		<b>PROTECTION CLASS</b>	III
<b>Dimensions</b>		<b>HOUSING COLOUR</b>	white
<b>height:</b> 30mm		<b>INSTALLATION OPENING LENGHT IN MM</b>	620
<b>length:</b> 620mm		<b>INPUT VOLTAGE SPAN</b>	37-40 DC
<b>width:</b> 620mm		<b>WARRANTY IN YEARS</b>	5
		<b>L80/B10</b>	50000
		<b>SUITABLE FOR MOUNTING</b>	Yes
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	37-40 DC
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>LIFETIME L80/B10 AT 25°C</b>	50000
		<b>ETIM GROUP IDENTIFICATION NUMBER</b>	EC002892

<b>WITH ILLUMINANT</b>	Yes
<b>MATERIAL COVER</b>	Plastic matt/satinized
<b>TYPE OF CONTROL GEAR</b>	-
<b>WITH CONTROL GEAR</b>	No
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	Yes
<b>DIMMING DALI</b>	Yes
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	Yes
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	Yes
<b>DIMMING WITH PUSH-BUTTON</b>	Yes
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>IMPACT STRENGTH</b>	IK02
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>TYPE OF WIRING</b>	-
<b>CONNECTION TYPE</b>	Plug
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	Yes
<b>LAMP TYPE</b>	LED not exchangeable
<b>DIMMING DALI-2</b>	Yes
<b>DIMMING PHASE CUT-ON</b>	Yes
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE</b>	C
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>TYPE OF GRID</b>	None
<b>BEAM ANGLE</b>	Extreme wide beam >80°
<b>DEGREE OF PROTECTION (NEMA)</b>	Other