


PRODUCT NO. 5423-030080

DOTLUX LED staircase light EASYSTAIR 1.5 W 3000K silver



to the product page

- Thanks to its compact design, the screw-on step light fits into all appliance boxes/terminal boxes for cavity walls and flush-mounted installation
- Quick and uncomplicated installation thanks to the integrated 230V power supply unit and magnetic cover
- Space-saving through-wiring with integrated push-in terminal block
- Easy to align thanks to four large keyholes with additional support surface for spirit levels
- Glare-free illumination of steps thanks to concealed arrangement of the illuminated surface with only 1.5 W energy consumption
- Available in 3 different colors

WEIGHT IN KG	0.117
POWER CONSUMPTION IN WATTS	1,5
NET LUMINOUS FLUX IN LUMENS	70
LUMEN PER WATT	47

Dimensions

length: 82mm
diameter: 150mm
width: 82mm
height: 43mm

BEAM ANGLE	75
PROTECTION CLASS (IP)	IP44
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 40.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,4
INRUSH CURRENT IN A	0
IK PROTECTION	IK04
LUMEN PER WATT	47
PROTECTION CLASS	II
VOLTAGE TYPE	AC
SUITED FOR EMERGENCY LIGHTING	No
INSTALLATION OPENING WIDTH IN MM	53
INSTALLATION OPENING DIAMETER IN MM	53
INSTALLATION OPENING LENGHT IN MM	53
WARRANTY IN YEARS	5
L80/B10	40000
RATED CURRENT	0
SUITABLE FOR SURFACE MOUNTING	No
SUITABLE FOR MOUNTING	Yes
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required

MOUNTING LOCATION	Indoor
LIFETIME L80/B10 AT 25°C	40000
ETIM GROUP IDENTIFICATION NUMBER	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR LIGHT LINE CONFIGURATION	Yes
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
LAMP HOLDER	-
MATERIAL COVER	-
TYPE OF GRID	-
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK04
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING WITH MOVEMENT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No

COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	1.5
LAMP TYPE	Compact fluorescent lamp
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	F
COLOUR OF LIGHT ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
SURFACE PROTECTION HOUSING	Lacquered
LIGHT OUTLET	Direct/indirect
LUMINOUS FLUX ADJUSTABLE	Continuously variable
LIGHT SHARING	Symmetric/asymmetric
BEAM ANGLE	Wide beam 41-80°
DEGREE OF PROTECTION (NEMA)	4x
HOUSING COLOUR	silver