

PRODUCT NO. 3671-499120

DOTLUX LED luminaire LUNAsilver-exit Ø490mm 33W COLORselect IP44



to the product page

1. Decorative ring made of high quality brushed aluminum
2. Cozy atmosphere due to indirect light components
3. Shadow-free light distribution with very stable PMMA cover IK07
4. Constant light output due to large-area aluminum core board
5. Easy installation, thanks to through-wireable luminaire terminal block
6. Sustainable, repairable product design

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3671-399160
WEIGHT IN KG	1.5
NET LUMINOUS FLUX IN LUMENS	3240/3730/3620
POWER CONSUMPTION IN WATTS	33
LUMEN PER WATT	98/113/110

Dimensions

diameter: 490mm
height: 115mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP44
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
RANGE OF SENSOR	0
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,95
IK PROTECTION	IK06
BATTERY RUNTIME	3h
LUMEN PER WATT	98/113/110
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	yes
PICTOGRAM INCLUDED	No
INSTALLATION OPENING WIDTH IN MM	0
INSTALLATION OPENING DIAMETER IN MM	0
INSTALLATION OPENING LENGHT IN MM	0
INPUT VOLTAGE SPAN	186-240
WARRANTY IN YEARS	5
L80/B10	50000
RATED CURRENT	0.17
DIMMING WITHOUT DIMMER	No
ENABLED LICENSED PRODUCT	Yes

INPUT VOLTAGE RANGE LUMINAIRE	186-240
SELF-TEST	Automatic self-test
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GROUP IDENTIFICATION NUMBER WITH ILLUMINANT	EC001957 Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	0
LAMP HOLDER	without
TYPE OF CONTROL GEAR	LED operating device current-controlled
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK06
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Ending
CONNECTION TYPE	Plug connection
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED not exchangeable
MOUNTING METHOD	surface mounted
WITH REMOTE CONTROL	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	E
LIGHT DISTRIBUTOR	None
MATERIAL COVER	Other