

PRODUCT NO. 5447-030131

DOTLUX LED floodlight HLFsport 1200W 3000K 1-10V dimmable 131*24° beam angle

















to the product page



- Optimized, asymmetric light control enables glare-free game operation and insect protection ULR<0 with reduced number of floodlights at the same time
- Protection of neighbors from stray light due to special lens geometry
- Corrosion-resistant, powder-coated cast aluminum housing with pressure compensation and high IP/IK protection (IP66/IK08)
- 1-10V dimmable and therefore compatible with our radio receiver Art. 5007-1 ideal for retrofitting existing installations
- 7 years DOTLUX warranty with an above average lifetime: L80>90.000h
- Very high operational safety with integrated overvoltage protection 20kV
- This luminaire is flicker-free and therefore also suitable for high-definition (HD) television recordings
- Sustainable product design due to easily replaceable components
- Other light colors can be ordered from 1pc onwards

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP66
		LIGHT COLOR	white
WEIGHT IN KG	24.48	INPUT VOLTAGE	220 - 240 V AC
POWER CONSUMPTION IN WATTS	1200	SERVICE LIFE	approx. ca. 90.000 h at 25° C
NET LUMINOUS FLUX IN LUMENS	148850	COLOR TEMPERATURE IN KELVIN	3000
LUMEN PER WATT	124	COLOR-RENDERING-INDEX	CRI > 70
		POWER FACTOR	0,92
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	124
Dimensions		PROTECTION CLASS	1
		HOUSING COLOUR	black
length: 702mm		SWITCH CYCLES	>180,000
width: 369mm		OVERVOLTAGE PROTECTION	20000
height: 681mm		INPUT VOLTAGE SPAN	220-240
		WARRANTY IN YEARS	7
		INPUT VOLTAGE RANGE LUMINAIRE	220-240
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GROUP IDENTIFICATION NUMBER	EC001744

MATERIAL COVER

NO DIM FUNCTION

COLOUR CONSISTENCY (MCADAM

DIMMING 1-10 V

ELLIPSE)

Glass transparent

Yes

Νo

SDCM6



only relevant in Germany

COVERING OF THE LUMINAIRE WITH
THERMALLY INSULATING MATERIAL
POSSIBLE

COMPATIBLE WITH APPLE HOMEKIT

COMPATIBLE WITH GOOGLE
ASSISTANT

COMPATIBLE WITH AMAZON ALEXA

PULSE DURATION IN µS

NO

ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE

COLOUR OF LIGHT ADJUSTABLE

No

BEG FUNDING