


PRODUCT NO. 5770

LED power supply CC 6W 250mA 24V

Wiring diagram
Anschlußbild



Hot plug-in or secondary switching is not permitted.
Das Anschließen im Betrieb oder sekundäres Schalten ist nicht erlaubt.

The maximum secondary wire length is 2 m.
Die maximale sekundäre Leitungslänge beträgt 2 m.



to the product page

- Direct current output with constant output voltage of 24V
- Suitable for class II luminaires
- Small housing
- Strain reliefs for independent use
- Average service life 50,000 h
- 5 year guarantee
- Short-circuit & open-circuit proof
- Automatic switch-off in case of overtemperature
- Overload protection
- SELV

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.04	INPUT VOLTAGE	176 - 240 V AC/DC
		SERVICE LIFE	approx. 100,000 h at 25°C
		PROTECTION CLASS	II
		SUITED FOR EMERGENCY LIGHTING	No
		SWITCH CYCLES	> 100.000
		OUTPUT VOLTAGE	24
		WARRANTY IN YEARS	5
		DIMMING WITHOUT DIMMER	No
		ETIM GROUP IDENTIFICATION NUMBER	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No
		DIMMING TOUCH AND DIM	No

Dimensions

length: 65mm

width: 39mm

height: 20mm

DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	No
CONSTANT LIGHT OUTPUT (CLO)	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR CONSTANT VOLTAGE	Yes
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR DC-VOLTAGE (PRIMARY SIDE)	No
SUITABLE FOR CONSTANT CURRENT	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
BEG FUNDING	Only relevant in Germany