

PRODUCT NO. 5997-030110

**DOTLUX LED indoor wall light FLAME 8W 3000K white**



to the product page

- Modern, decorative wall light with direct and indirect lighting
- Unique design with great decorative effect
- Excellent heat management thanks to aluminum housing ensures a long service life
- Housing color similar to RAL 9016

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	110
<b>WEIGHT IN KG</b>	0.551	<b>PROTECTION CLASS (IP)</b>	IP20
<b>POWER CONSUMPTION IN WATTS</b>	8	<b>LIGHT COLOR</b>	white
<b>NET LUMINOUS FLUX IN LUMENS</b>	632	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>LUMEN PER WATT</b>	79	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	3000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 80
		<b>POWER FACTOR</b>	0,88
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK00
		<b>LUMEN PER WATT</b>	79
		<b>PROTECTION CLASS</b>	I
		<b>VOLTAGE TYPE</b>	AC
		<b>HOUSING COLOUR</b>	white
		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
		<b>WARRANTY IN YEARS</b>	3
		<b>L80/B10</b>	54000
		<b>SIMILAR TO RAL-COLOUR</b>	9006
		<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
		<b>SUITABLE FOR MOUNTING</b>	No
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>MOUNTING LOCATION</b>	Indoor
		<b>LIFETIME L80/B10 AT 25°C</b>	54000
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	81000
		<b>ETIM GROUP IDENTIFICATION NUMBER</b>	EC002892

**Dimensions**

**length:** 120mm

**width:** 140mm

**height:** 70mm

<b>SUITABLE FOR WALL MOUNTING</b>	Yes
<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
<b>SUITABLE FOR CEILING MOUNTING</b>	No
<b>SUITABLE FOR LIGHT LINE CONFIGURATION</b>	No
<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
<b>MATERIAL COVER</b>	Plastic matt/satinized
<b>WITH CONTROL GEAR</b>	No
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	Yes
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	Yes
<b>DIMMING PHASE CUT-OFF</b>	Yes
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	No
<b>IMPACT STRENGTH</b>	IK00
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>WITH AIR SLOTS</b>	No
<b>FILAMENT TEST ACCORDING TO IEC 60695-2-11</b>	750 °C - 30 s
<b>TYPE OF WIRING</b>	Ending
<b>LUMINOUS FLUX ADJUSTABLE</b>	Positions
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	No
<b>SUITABLE FOR LAMP POWER IN W</b>	8
<b>LAMP TYPE</b>	LED not exchangeable
<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	81000

<b>LIFETIME L90/B10 AT 25°C</b>	27000
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE</b>	F
<b>LIGHT SHARING</b>	Asymmetric
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>TYPE OF GRID</b>	Matt
<b>LIGHT OUTLET</b>	Direct/indirect
<b>SURFACE PROTECTION HOUSING</b>	Plastic-coated
<b>LIGHT DISTRIBUTOR</b>	Other
<b>BEAM ANGLE</b>	Extreme wide beam >80°
<b>CONNECTION TYPE</b>	Other