

PRODUCT NO. 6161-040170

DOTLUX Refurbishment light QUICK-FIXadapt 29W 4000K



to the product page

- Universal luminaire-in-luminaire system for quick and easy replacement of all conventional light sources in ceiling and wall luminaires
- Tool-free replacement of the QUICK-FIXadapter even by a non-specialist thanks to DC system plug
- Special lenses with 170° beam angle of the luminaire also possible by a non-specialist
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- the QUICKFIX-adapt can be set up to 700mA with the matching 5068-1 power supply unit.
- inner diameter 25cm
- Outer diameter 30cm

Power consumption and net luminous flux of the luminaire with different operating currents:

- 12W@ 300mA = 2220lm = 185lm/W
- 14W@ 350mA = 2570lm = 184lm/W
- 16W@ 400mA = 2925lm = 183lm/W
- 18W@ 450mA = 3290lm = 183lm/W
- 23W@ 550mA = 3930lm = 171lm/W
- 25W@ 600mA = 4140lm = 166lm/W
- 27W@ 650mA = 4600lm = 170lm/W
- 29W@ 700mA = 4850lm = 167lm/W

SUCCESSION ARTICLE	-	BEAM ANGLE	170
WEIGHT IN KG	0.107	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	29	COLOR TEMPERATURE IN KELVIN	4000
NET LUMINOUS FLUX IN LUMENS	4850	POWER FACTOR	0,9
LUMEN PER WATT	167	LUMEN PER WATT	167
		WARRANTY IN YEARS	3
		L80/B10	50000
		LIFETIME L80/B10 AT 25°C	50000
		EXTERNAL DRIVER REQUIRED	Yes
Dimensions		LED OPERATING CURRENT IN MA	700
height: 20mm		SHAPE	Round
diameter: 300mm			