

PRODUCT NO. 3143-24

LED power supply IP67 Proline 24 V/DC, 25A, 600W with MM mark







to the product page



LED Power Supply IP67 High Quality 24 V/DC, 25A, 600 W

• FEATURES:

- o Universal input
- o overload protection by current limiting, auto recovery
- $\circ\;$ protected against short circuit, overload, overvoltage
- o IP67, for indoor and outdoor applications
- o for LED and lighting applications
- o UL1310 Class 2
- o dimmable
- o EN61000-3-2, Class C, EN55015, EN61347-1, EN61347-2-13

• TECHNICAL DATA:

- o Input voltage range: 90...264V/AC (47...63Hz) 127...370V/ DC
- o Inrush current max: 65A
- o Overload protection: 95...1080 %.
- Insulation voltage (I/P-O/P):
- o I/P-O/P: 3750V / AC
- o I/P-EF: 2000V / AC
- o O/P-FG: 500 V / AC
- Operating temperature range: -30... 70°C
- o Weight: 1000 g

SUCCESSION ARTICLE	-	INRUSH CURRENT IN A	0
		SUITED FOR EMERGENCY LIGHTING	No
WEIGHT IN KG	3.748	OUTPUT VOLTAGE	24
		WARRANTY IN YEARS	7
		DIMMING WITHOUT DIMMER	No
		ETIM GROUP IDENTIFICATION NUMBER	EC002710
Dimensions		DIMMING 0-10 V	Yes
		DIMMING 1-10 V	No
width: 144mm		DIMMING DALI	No
height: 49mm		DIMMING DMX	No
length: 280mm		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No



DIMMING PROGRAMMABLE No DIMMING RF No DIMMING SINE WAVE REDUCTION No **DIMMING TOUCH AND DIM** No DIMMING ZIGBEE No DIMMING WITH PUSH-BUTTON Yes NO DIM FUNCTION No SUITABLE FOR EMERGENCY LIGHTING No **OPERATION BY BLUETOOTH** No **COMPATIBLE WITH CASAMBI** No COMPATIBLE WITH APPLE HOMEKIT No COMPATIBLE WITH GOOGLE No ASSISTANT **COMPATIBLE WITH AMAZON ALEXA** No MODEL Other SUITABLE FOR CONSTANT VOLTAGE No SUITABLE FOR OUTDOOR USE Yes SUITABLE FOR DC-VOLTAGE (PRIMARY No SIDE) SUITABLE FOR CONSTANT CURRENT No HOUSING Metal housing DIMMING PHASE CUT-ON No DIMMING GPRS No

0

Only relevant in Germany

PULSE DURATION IN µS

BEG FUNDING