

PRODUCT NO. 3456

DOTLUX LED street light BELUGAmicro 38W 4000K without pole adapter















to the product page

- Protection class I with integrated overvoltage protection (10,000 V)
- Variety of adapters enables mounting on all pole diameters
- The multilayer lens optics with CREE® LEDs enable uniform light distribution
- Solid cast aluminum housing in RAL 7022 with impact resistance class IK09
- Reliable and highly efficient LED driver with a service life of > 80,000h ensures low maintenance costs

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	2407
WEIGHT IN KG	3.2
POWER CONSUMPTION IN WATTS	38
NET LUMINOUS FLUX IN LUMENS	4560
LUMEN PER WATT	120

length: 405mm width: 190mm height: 92mm

BEAM ANGLE	135x50
PROTECTION CLASS (IP)	IP66
LIGHT COLOR	white

 INPUT VOLTAGE
 176 - 240 V AC/DC

 SERVICE LIFE
 approx. 80.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 4000 **COLOR-RENDERING-INDEX** CRI > 75

MAST SUPPORT depending on adapter

 POWER FACTOR
 0.955

 INRUSH CURRENT IN A
 0

 IK PROTECTION
 IK09

 LUMEN PER WATT
 120

 PROTECTION CLASS
 I

 HOUSING COLOUR
 gray

 SWITCH CYCLES
 > 160.000

 OVERVOLTAGE PROTECTION
 up to 10000 V

WARRANTY IN YEARS 7
ASSORTMENT Proline

ENERGY EFFICIENCY CLASS

ACCORDING TO EU REGULATION not required

2019/2015

ETIM GROUP IDENTIFICATION NUMBER EC000062

MATERIAL COVER Glass transparent

DIMMING 0-10 V No
DIMMING 1-10 V No
DIMMING DALI No
DIMMING DMX No



DIMMING DSI No DIMMING POTENTIOMETER No (INTEGRATED) DIMMING LINESWITCH No DIMMING MANUFACTURER'S No PROPRIETARY SYSTEM **DIMMING MAINS VOLTAGE** No MODULATION DIMMING PHASE CUT-OFF No **DIMMING PROGRAMMABLE** No DIMMING RF No **DIMMING SINE WAVE REDUCTION** No DIMMING TOUCH AND DIM No DIMMING ZIGBEE No DIMMING WITH PUSH-BUTTON No NO DIM FUNCTION Yes COLOUR CONSISTENCY (MCADAM SDCM6 ELLIPSE) IMPACT STRENGTH IK09 **COMPATIBLE WITH APPLE HOMEKIT** No **COMPATIBLE WITH GOOGLE** No **ASSISTANT COMPATIBLE WITH AMAZON ALEXA** No DIMMING PHASE CUT-ON No DIMMING GPRS Nο PULSE DURATION IN µS only relevant in Germany **BEG FUNDING ENERGY EFFICIENCY CLASS OF THE** LIGHT SOURCE OF A LUMINAIRE