

DOTLUX LED-Streifen 48W 10mm 5000K IP66 5m-Rolle inkl. 50cm Anschlusskabel beidseitig

Bestellnummer: 3943-050IP665M

- Comfortable and natural light due to extra high color rendering RA>92.
- Uniform color temperature due to 3-Step Mac Adam Binning and specially extruded IP66 protective cover
- Very densely arranged LEDs allow homogeneous illuminated areas at smallest distances
- Secure Solder Connect Technology prevents hairline cracks and cold solder Joints
- Reinforced conductor paths ensure uniform brightness
- Original 3M adhesive tape provides strong hold
- 15 cm connection cable pre-mounted on one side

Leistungsaufnahme in Watt: 48; Lichtstrom netto in Lumen: 4200; Abstrahlwinkel: 120; Schutzart (IP): IP66; Lichtfarbe: weiß;
Nutzlebensdauer: ca. 50.000 h bei 25°C; Farbtemperatur in Kelvin: 5000; Farbwiedergabeindex: Ra > 92; Anzahl der LED/m: 140; Trennbar
nach mm: 50; Lichtstrom lm/m: 840; Kleinster Biegeradius in mm: 25; Eingangsspannungsbereich: 24 V DC; Garantie in Jahren: 7;
Eingangsspannungsbereich Leuchte: 24 V DC; Energieeffizienzklasse der Lichtquelle nach EU-Richtlinie 2019/2015: F; ETIM Gruppen-ID:
ECC002706; Kompatibel mit Apple HomeKit: Nein; Kompatibel mit Google Assistant: Nein; Kompatibel mit Amazon Alexa: Nein; BEG
Förderung: Nein; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Farbtemperatur einstellbar: Nein
Breite: 10mm