

PRODUCT NO. 3944-027IP205M

DOTLUX LED strip 96W 10mm 2700K IP20 5m roll incl. 50cm connection cable both sides












to the product page

- Cozy and natural light due to extra high color rendering RA>92
- Consistent color temperature due to 3-step Mac Adam binning
- Very densely arranged LEDs enable homogeneous luminous surfaces at smallest distances
- Secure Solder Connect Technology prevents hairline cracks and cold solder joints
- Reinforced conductor paths ensure uniform brightness
- Original 3M adhesive tape provides strong hold
- 15 cm connection cable pre-mounted on one side



at 25°C

| SUCCESSION ARTICLE | - | BEAM ANGLE | 120 |
|-----------------------------|--------|-----------------------------|--------------------|
| PREDECESSOR ARTICLE | 1979-3 | PROTECTION CLASS (IP) | IP20 |
| | | LIGHT COLOR | white |
| WEIGHT IN KG | 0.11 | SERVICE LIFE | approx. 50.000 h a |
| POWER CONSUMPTION IN WATTS | 96 | COLOR TEMPERATURE IN KELVIN | 2700 |
| NET LUMINOUS FLUX IN LUMENS | 8750 | COLOR-RENDERING-INDEX | CRI > 92 |
| LUMEN PER WATT | 91 | AMOUNT OF LED/M | 238 |
| | | SEVERABLE BY MM | 30 |
| | | TC TEMPERATURE IN °C | 67 |
| | | OUTPUT W/M | 19.2 |

Dimensions

length: 5000mm width: 10mm height: 1mm

ACCORDING TO EU REGULATION F
2019/2015
ETIM GROUP IDENTIFICATION NUMBER EC002706

COMPATIBLE WITH GOOGLE
ASSISTANT
COMPATIBLE WITH AMAZON ALEXA
No

BEG FUNDING Only relevant in Germany

Nο

ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE COLOUR OF LIGHT ADJUSTABLE