

## **PRODUCT NO.** 3944-040IP205M

## DOTLUX LED strip 96W 10mm 4000K IP20 5m roll incl. 50cm connection cable on both sides












to the product page

CA A CONTRACTOR OF THE CONTRAC

- Cozy and natural light due to extra high color rendering RA>92
- Consistent color temperature due to 3-step Mac Adam binning
- Very densely arranged LEDs enable homogeneous luminous surfaces at smallest distances
- Secure Solder Connect Technology prevents hairline cracks and cold solder joints
- Reinforced conductor paths ensure uniform brightness
- Original 3M adhesive tape provides strong hold
- 15 cm connection cable pre-mounted on one side



50.000 h at 25°C

SUCCESSION ARTICLE	-	BEAM AI
PREDECESSOR ARTICLE	1982-3	PROTECT
		LIGHT CO
WEIGHT IN KG	0.145	INPUT V
POWER CONSUMPTION IN WATTS	96	SERVICE
NET LUMINOUS FLUX IN LUMENS	9000	COLOR T
LUMEN PER WATT	94	COLOR-R

## Dimensions

length: 5000mm width: 10mm height: 2mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	24V / DC
SERVICE LIFE	approx. 5
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 92

AMOUNT OF LED/M 238 **SEVERABLE BY MM** 30 TC TEMPERATURE IN °C 67 OUTPUT W/M 19,2 **LUMEN PER WATT** 94 LIGHT FLUX LM/M 1800 **SMALLEST BEND RADIUS IN MM** 25 INPUT VOLTAGE SPAN 24 V DC **WARRANTY IN YEARS** INPUT VOLTAGE RANGE LUMINAIRE 24 V DC

ENERGY EFFICIENCY CLASS
ACCORDING TO EU REGULATION
2019/2015

ETIM GROUP IDENTIFICATION NUMBER EC002706

COMPATIBLE WITH APPLE HOMEKIT No
COMPATIBLE WITH GOOGLE
ASSISTANT No

COMPATIBLE WITH AMAZON ALEXA No

**BEG FUNDING** Only relevant in Germany

ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE



COLOUR OF LIGHT ADJUSTABLE

No