

PRODUCT NO. 2814-350045

**DOTLUX LED strip lighting system LINEAclick 50W 5000K narrow beam dimmable DALI Made in Germany**



to the product page

- Continued use of your existing mounting rail system
- Mounting without mechanical intervention in the mounting rail system with heat-resistant neodymium
  - magnetic holders incl. safety rope
- Independent, integrated cable system with quick connectors
- Optimized transmittance of the patented LINEAclick lens from DOTLUX®
- Shadow-free light distribution thanks to innovative lens design
- Perfect cooling of the LED module thanks to aluminum core board
- LM80 certified LEDs with 40% current consumption
- Suitable for central battery (only DALI article no. 2814-350045 and 2813-450160)

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	45
<b>PREDECESSOR ARTICLE</b>	2814	<b>PROTECTION CLASS (IP)</b>	IP40
<b>WEIGHT IN KG</b>	2.455	<b>LIGHT COLOR</b>	white
<b>POWER CONSUMPTION IN WATTS</b>	50	<b>INPUT VOLTAGE</b>	176 - 240 V AC/DC
<b>NET LUMINOUS FLUX IN LUMENS</b>	8500	<b>Service life</b>	
<b>LUMEN PER WATT</b>	170	<b>COLOR TEMPERATURE IN KELVIN</b>	5000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 83
		<b>POWER FACTOR</b>	0,98
		<b>INRUSH CURRENT IN A</b>	0
		<b>LUMEN PER WATT</b>	170
		<b>PROTECTION CLASS</b>	I
<b>Dimensions</b>		<b>VOLTAGE TYPE</b>	AC/DC
<b>length:</b> 1530mm		<b>HOUSING COLOUR</b>	Aluminium
<b>width:</b> 73mm		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
<b>height:</b> 61mm		<b>SWITCH CYCLES</b>	> 200.000
		<b>WARRANTY IN YEARS</b>	7
		<b>L80/B10</b>	100000
		<b>RATED CURRENT</b>	2.9
		<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
		<b>SUITABLE FOR MOUNTING</b>	No
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>LIFETIME L80/B10 AT 25°C</b>	100000
		<b>ETIM GROUP IDENTIFICATION NUMBER</b>	EC002892

WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	-
MATERIAL COVER	Plastic, transparent
TYPE OF GRID	-
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	Yes
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	Yes
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
TYPE OF WIRING	Through wiring included
CONNECTION TYPE	Bus
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	50
LAMP TYPE	LED exchangeable

<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING DALI-2</b>	Yes
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE</b>	C
<b>LIGHT OUTLET</b>	Direct
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>LIGHT DISTRIBUTOR</b>	Other
<b>BEAM ANGLE</b>	Wide beam 41-80°
<b>SURFACE PROTECTION HOUSING</b>	Other