

PRODUCT NO. 4252-12

LED power supply CV 12V DC 60W 5A IP67



to the product page



- Power supply in aluminum housing
- Overload protection by shutdown
- IP67 protected housing
- not dimmable
- with open cable ends

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP67
WEIGHT IN KG	0.696	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	60	OUTPUT CURRENT IN A	5
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	85
Dimensions		OUTPUT VOLTAGE	12 DC
length: 180mm		INPUT VOLTAGE SPAN	100-305 AC / 142-431 DC
width: 63mm		WARRANTY IN YEARS	5
height: 36mm		INPUT VOLTAGE RANGE LUMINAIRE	100-305 AC / 142-431 DC
		ETIM GROUP IDENTIFICATION NUMBER	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No

DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany